


DAVIS

Deco Contract

A portfolio that simplifies designers selection process with coordinated styles and colors for seamless results.
High resistance to abrasion, light and stain.
Long lasting / designed for life.

Composition	72% PVC, 28% CO
Width	1,37 – 1,40 m
Weight	760 g/m ² ± 5%
Thickness	0,95 – 1,15 mm
Mechanical properties	Tensile strength ISO 1421-met. 1 Tear strength ISO 4674-1-met. B Adhesion ISO 2411
Abrasion resistance	≥ 150000 Martindale cycles grade 2 ISO 5470-2
Colour fastness to	Rubbing ISO 105-X12 Ethyl alcohol ≥70% Bleach (4.5% chlorine) Acid and alkaline perspiration ISO 105-E04 Saliva DIN 53160-1 Artificial blood Artificial urine
Light fastness	Artificial light ISO 105-B02
Fire resistance	FMVSS302 EN 1021-1+2 NF P 92-503 M2 BS 5852 Crib5 IMO 2010 FTP Code Part 8 UNI 9175 1.IM
Antibacterial / Antifungal	Sanitized [®] JIS Z 2801, ISO 846 A




HOSPITALITY



HEALTHCARE



OFFICE



PUBLIC SPACES



FITNESS



RESTAURANT



RETAIL



RESIDENTIAL



RECREATIONAL
VEHICLES

Easy to clean with mild detergent and a damp cloth.

Free from harmful substances / Phthalate free.

Manufactured in compliance with EU regulation REACH ((EC) no 1907/2006).

Suitable for toys and childcare articles; meets Directive 2005/84/EC requirements.



Monteiro, Ribas – Revestimentos, SA
Circunvalação, 9020 Apartado 52511 | 4202-351 Porto, Portugal
+351 228 338 640 | monteirofabrics@mri.pt
www.monteirofabrics.com



Management
System
ISO 9001:2015
ISO 14001:2015



www.tuv.com
ID: 9105064640